

SPECIFICATION

TRASCO ENAMEL PAINT ALKYD BASED

TYPE	A versatile alkyd resin based paint, which cures by air oxidation
USES	Decorative paint for prime wooden and metal surfaces both interior and exterior <ul style="list-style-type: none">• Dry timber• Plywood• Ferrous metals• Non-ferrous metals
FEATURES	<ul style="list-style-type: none">• Excellent hiding power• Excellent durability• Excellent weathering resistance• High gloss finishing• Excellent wash ability• Easy application

APPLICATION DATA

APPLICATION METHOD	Air-spray, Brush or Roller
DILUTION	Product is ready for use. Maximum dilution up to 10% if necessary
SPREADING RATE	8 - 11 m ² / Litre / Coat
SURFACE PREPARATION	Surface must be clean, dry & grease free.
DRY FILM THICKNESS	30 microns / coat
DRYING TIME	Touch dry : 1 – 2 hours at 30 °C Hard dry : 6 – 8 hours at 30 °C
OVERCOATING INTERVAL	Minimum 10 hours at 30 °C
STORAGE	Close tightly after each used and always store in a cool, dry and clean environment

GENERAL INFORMATION

SPECIFIC GRAVITY	1.00 – 1.20 Kg / Litre
PACKING SIZE	4 litre and 20 litre can
RECOMMENDED	Alkyd Base Primer / Suitable Primer undercoat
FLASHPOINT	35 °C