



# TRASCO COATING PTE LTD

30 Joo Koon Circle Singapore 629059  
Tel: (65) 6897 8282 Fax: (65) 68978228  
www.trasco.com.sg  
UEN No.: 199804876H GST Reg. No.: 19-9804876-H



## TRASCO ROADLINE PAINT

TYPE	A single component road marking paint based on thermoplastic resin.
USES	Road marking paint for concrete and tar surfaces.
FEATURES	<ul style="list-style-type: none"><li>• Fast drying</li><li>• Tough film</li><li>• Good dirt pick-up resistance</li><li>• Excellent water resistance</li><li>• Good adhesion to substrate</li><li>• Good coverage</li></ul>
COLOUR	White, yellow, black and red

---

### **APPLICATION DATA**

---

APPLICATION METHOD	Air/Airless Spray, Brush, Roller
DILUTION	Ready for use. If required, Max 20%-50% by weight dilution with Trasco Roadline Thinner
SPREADING RATE	Approx. 8 - 9 m <sup>2</sup> / ltr / coat
SURFACE PREPARATION	Surface must be grease free, clean and dry.
DRY FILM THICKNESS	Approx. 50 microns/ coat
OPACITY (CONTRAST RATIO)	Min. 70%
“NO PICK-UP” DRYING TIME	Max.15 mins at 30° C
OVERCOATING INTERVAL	Min. 15 mins at 30° C Max. indefinite
STORAGE	Store in cool, dry and area.

---

### **GENERAL INFORMATION**

---

SPECIFIC GRAVITY	1.33 – 1.42 kg/ ltr
SOLID CONTENT (BY WEIGHT)	Min. 60%
VISCOSITY	75 +/- 5 KU @ 25° C
PACKING SIZE	5 liters / 20 liters
RECOMMENDED PAINTING SYSTEM	1 – 2 coats Trasco Roadline Paint
FLASHPOINT	25° C